

# WEATHER SMART

Tire Size	LI/SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
225/45R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
215/50R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
225/50R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
215/55R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
225/55R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
235/55R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
225/60R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
215/65R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
225/65R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
235/65R17*	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
225/40R18 XL	92V	600 A A	100U44412	8.00	7.5 - 9.0	1389	50	11	24.9	9.2	22.7	BSW
245/40R18 XL	97V	600 A A	100U44422	8.50	8.0 - 9.5	1609	50	11	25.6	9.9	25.1	BSW
225/45R18 XL	95V	600 A A	100U44413	7.50	7.0 - 8.5	1521	50	11	25.9	9.1	23.1	BSW
225/60R18	100H	600 A A	100U44416	6.50	6.0 - 8.0	1764	44	11	28.3	9.6	28.1	BSW
235/45R18	94V	600 A A	100U44417	8.00	7.5 - 9.0	1477	44	11	26.3	9.7	24.8	BSW
245/45R18 XL	100V	600 A A	100U44423	8.00	7.5 - 9.0	1764	50	11	26.5	9.8	25.9	BSW
225/50R18	95V	600 A A	100U44414	7.00	6.0 - 8.0	1521	44	11	26.7	9.7	25.9	BSW
235/50R18	97V	600 A A	100U44418	7.50	6.5 - 8.5	1609	44	11	27.1	10	27.1	BSW
215/55R18	95H	600 A A	100U44411	7.00	6.0 - 7.5	1521	44	11	27.1	9.3	24.9	BSW
235/55R18	98V	600 A A	100U44415	7.00	6.0 - 8.0	1653	44	11	27.5	9.6	26.9	BSW
225/55R18	100V	600 A A	100U44419	7.50	6.5 - 8.5	1764	44	11	27.9	9.9	29.0	BSW
235/60R18	103V	600 A A	100U44420	7.00	6.5 - 8.5	1929	44	11	28.7	10	29.0	BSW
245/60R18	105V	600 A A	100U44424	7.00	7.0 - 8.5	2039	44	11	29.2	10.4	31.3	BSW
235/65R18	106V	600 A A	100U44421	7.00	6.5 - 8.5	2094	44	11	29.6	10	31.3	BSW
235/40R19 XL	96V	600 A A	100U44426	8.50	8.0 - 9.5	1565	50	11	26.3	9.6	24.9	BSW
245/40R19 XL	98V	600 A A	100U44440	8.50	8.0 - 9.5	1653	50	11	26.7	9.9	25.4	BSW
235/45R19	95H	600 A A	100U44427	8.00	7.5 - 9.0	1521	44	11	27.2	9.7	25.6	BSW
245/45R19 XL	102V	600 A A	100U44430	8.00	7.5 - 9.0	1874	50	11	27.6	9.9	27.3	BSW
235/50R19	99H	600 A A	100U44428	7.50	6.5 - 8.5	1709	44	11	28.1	10	28.2	BSW
255/50R19 XL	107V	600 A A	100U44432	8.00	7.0 - 9.0	2149	50	11	28.9	10.8	31.3	BSW
225/55R19 XL	103V	600 A A	100U44425	7.00	6.0 - 8.0	1709	50	11	28.7	9.6	28.2	BSW
235/55R19	101V	600 A A	100U44429	7.50	6.5 - 8.5	1819	44	11	29	10	29.6	BSW
245/55R19	103V	600 A A	100U44431	7.50	7.0 - 8.5	1929	44	11	29.4	10.3	34.0	BSW
245/45R20 XL	103V	600 A A	100U44434	8.00	7.5 - 9.0	1929	50	11	28.5	9.9	28.665	BSW
255/45R20 XL	105V	600 A A	100U44441	8.50	8.0 - 9.5	2039	50	11	28.9	10.2	31.1	BSW
265/45R20 XL	108V	600 A A	100U44442	9.00	8.5 - 10.0	2205	50	11	29.1	10.6	31.3	BSW
245/50R20	102V	600 A A	100U44435	7.50	7.0 - 8.5	1874	44	11	29.5	10.3	31.1	BSW
255/50R20	105V	600 A A	100U44436	8.00	7.0 - 9.0	2039	44	11	29.8	10.8	33.0	BSW
265/50R20	107V	600 A A	100U44437	8.50	7.5 - 9.5	2149	44	11	29	11.3	34.7	BSW
235/55R20	102V	600 A A	100U44433	7.50	6.5 - 8.5	1874	44	11	30	10	30.9	BSW
255/55R20 XL	110V	600 A A	100U44438	8.00	7.0 - 9.0	2337	50	11	30.8	10.8	33.7	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade BSW Black Sidewall \*Coming soon

Giti reserves the right to change the construction, materials or specifications without notice or obligations

