

GitiXCURSION XT

Tire Size	LI/SR	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
265/70R17	115T	540 A B	100UA4306	8.00	7.0 - 9.0	2679	44	13.5	31.7	10.6	41	BSW
265/65R18	114T	540 A B	100UA4308	8.00	7.5 - 9.5	2601	44	13.5	31.8	10.7	43.7	BSW
275/65R18	116T	540 A B	100UA4310	8.00	7.5 - 9.5	2756	44	13.5	32	11	43.2	BSW
275/55R20 XL	117H	540 A B	100UA4311	8.50	7.5 - 9.5	2833	50	13.5	32	11.5	43.7	BSW
275/60R20	115H	540 A B	100UA4327	8.00	7.5 - 9.5	2679	44	13.5	32.9	11	44.5	BSW
245/65R17 XL	111T	640 A B	100UA4204	7.00	7.0 - 8.5	2403	50	13.5	29.8	9.8	42.3	BSW

LT Tire Size	LI/SR (s/d)	UTQG	Item Number	Measuring Rim	Rim Width Range	Max. Load	Max. Pressure	Tread Depth	Overall Diameter	Section Width	Weight	Sidewall
				inch	inch	lbs	psi	32nd	inch	inch	lbs	
35X12.50R17LT	125R	E/10	100UA4360	10.00	8.0 - 10.5	3640	65	18.5	34.8	12.5	70.1	BSW
33X12.50R18LT	122R	F/12	100UA4361	10.00	8.5 - 11.0	3305	80	18.5	32.8	12.5	63.9	BSW
35X12.50R18LT	128R	F/12	100UA4362	10.00	8.5 - 11.0	3970	80	18.5	34.8	12.5	69.2	BSW
33X12.50R20LT	119R	F/12	100UA4363	10.00	8.5 - 11.0	3000	80	18.5	32.8	12.5	62.2	BSW
35X12.50R20LT	125R	F/12	100UA4364	10.00	8.5 - 11.0	3640	80	18.5	34.6	12	62.4	BSW
35X12.50R22LT	121R	F/12	100UA4366	10.00	8.5 - 11.0	3195	80	18.5	34.8	12.5	65.3	BSW
LT245/75R16	120/116S	E/10	100UA4331	7.00	6.5 - 8.0	3042 / 2778	80	16	30.7	9.8	48.9	BSW
LT265/75R16	123/120S	E/10	100UA4332	7.50	7.0 - 9.0	3415 / 3085	80	16	31.9	10.5	54.2	BSW
LT245/70R17	119/116S	E/10	100UA4334	7.00	6.5 - 8.0	3000 / 2755	80	16	30.8	9.8	48.1	BSW
LT265/70R17	123/120S	E/10	100UA4336	8.00	7.0 - 9.0	3415 / 3085	80	16	31.2	10.2	48.3	BSW
LT285/70R17	126/123S	E/10	100UA4337	8.50	7.5 - 9.5	3750 / 3415	80	16	32.8	11	59.5	BSW
LT315/70R17	126/123S	E/10	100UA4338	9.50	8.0 - 10.5	3750 / 3415	80	16	34.7	12.7	68.1	BSW
LT245/75R17	121/118S	E/10	100UA4335	7.00	6.5 - 8.0	3195 / 2910	80	16	31.5	9.4	46.3	BSW
LT235/80R17	120/117R	E/10	100UA4333	6.50	6.0 - 8.0	3085 / 2835	80	16	32.1	9.3	48.7	BSW
LT275/65R18	123/120S	E/10	100UA4341	8.00	8.0 - 9.5	3415 / 3085	80	16	32.1	10.6	51.6	BSW
LT285/65R18	125/122S	E/10	100UA4343	8.50	8.5 - 10.0	3640 / 3305	80	16	32.8	11.5	58.6	BSW
LT265/70R18	124/121S	E/10	100UA4340	8.00	7.0 - 9.0	3525 / 3195	80	16	32.9	10.7	55.6	BSW
LT275/70R18	125/122S	E/10	100UA4342	8.00	7.0 - 9.0	3640 / 3305	80	16	33.2	10.5	47	BSW
LT295/70R18	129/126R	E/10	100UA4367	8.50	7.5 - 10.0	4080 / 3750	80	16	34.5	11.8	64.4	BSW
LT275/55R20	120/117T	E/10	100UA4345	8.50	8.0 - 9.5	3085 / 2835	80	16	32.1	11.2	54	BSW
LT265/60R20	121/118S	E/10	100UA4344	8.00	8.0 - 9.5	3195 / 2910	80	16	32.5	10.7	54.7	BSW
LT275/60R20	123/120S	E/10	100UA4346	8.00	8.0 - 9.5	3415 / 3085	80	16	33.2	11	56	BSW
LT285/60R20	125/122S	E/10	100UA4348	8.50	8.5 - 10.0	3640 / 3305	80	16	33.7	11.5	59.7	BSW
LT295/60R20	126/123S	E/10	100UA4349	8.50	8.5 - 10.5	3750 / 3415	80	16	34.2	11.8	68.8	BSW
LT275/65R20	126/123S	E/10	100UA4347	8.00	8.0 - 9.5	3750 / 3415	80	16	34.2	10.8	56.2	BSW
LT295/65R20	129/126S	E/10	100UA4350	8.50	8.5 - 10.5	4080 / 3750	80	16	35.4	11.8	72.3	BSW

LI Load Index SR Speed Rating XL Extra Load UTQG Uniform Tire Quality Grade BSW Black Side Wall

Giti reserves the right to change the construction, materials or specifications without notice or obligations

